


	A	B
SA3-32F	90	Φ268
SA3-22F	65	Φ200
SA3-21F	66	Φ186
SA3-20F	60	Φ174



	A	B
SA3-22FH	90	Φ200
SA3-32FH	118	Φ268



Model	SA3-22L	SA3-22LH	SA3-22FH	SA3-32FH	SA3-32F	SA3-22F	SA3-21F	SA3-20F
Rated power	20W	20W	6W	15W	15W	6W	6W	6W
Line voltage	100V	100V	100V	100V	100V	100V	100V	100V
Sensitivity (1m, 1W)	93±3dB	93±3dB	92±3dB	91±3dB	91±3dB	92±3dB	90±3dB	90±3dB
Frequency response	140-15kHz	140-15kHz	100-18kHz	150-18kHz	90-18kHz	100-18kHz	130-20kHz	135-18kHz
Dimension (mm)	Φ220*115	Φ220*150	Φ200*90	Φ268*118	Φ268*90	Φ200*65	Φ186*66	Φ174*60
Hole for mounting	Φ208	Φ208	Φ185	Φ205	Φ205	Φ185	Φ165	Φ155
Material	IRON	IRON	IRON	IRON	IRON	IRON	IRON	IRON
Weight (kg)	1.5	1.6	2.2	1.65	1.21	1.9	0.73	0.62
Speaker unit	6.5"	6.5"	6"	8"	8"	6"	5"	4"