

RACK MOUNT TYPE AMPLIFIERS

PMA-1240M/ 1360M

5 zones paging selectable for output

FEATURES

- PMA-1000 Series (high power amplifier).
- Power output: 240W/360W, RMS, output.
- Distortion: 1% at 1kHz rated power.
- 4 balance XLR-6.3 ϕ jack/mic sensitivity selectable and switchable 24V DC phantom supply.
- Over load & over current protection.
- One Main in & One Pre out.
- LED VU indicator.
- Tel, input & monitor output.
- AC 115V/230V input.
- DC: 24V



PMA-1240M

	PMA-1240M	PMA-1360M
Type:	240W RMS Mono-Table-top	360W RMS Mono-Table-top
RMS/MAX power:	240W/280W	360W/400W
Frequency response:	50Hz~15kHz (± 3 dB)	50Hz~15kHz (± 3 dB)
Total harmonic distortion:	$\leq 1\%$	$\leq 1\%$
S/N ratio:	Input 1-4 Mic: ≥ 60 dB(1~4) Line: ≥ 65 dB Aux in: ≥ 70 dB RCA Main in: ≥ 80 dB	Input 1-4 Mic: ≥ 60 dB(1~4) Line: ≥ 65 dB Aux in: ≥ 70 dB RCA Main in: ≥ 80 dB
Phantom supply on input:	(MIC 1~4) XLR. phantom DC 24V	(MIC 1~4) XLR. phantom DC 24V
Input/Sensitivity impedance:	Input 1-4 (balance) Mic: 1mV-4.5K Ω XLR + 6.3 ϕ	Input 1-4 (balance) Mic: 1mV-4.5K Ω XLR + 6.3 ϕ
Line:	100mV-210k Ω	100mV-210k Ω
Aux:	100mV-18k Ω	100mV-18k Ω
Main in:	775mV-10k Ω	775mV-10k Ω
Output(Ω):	COM, 4 Ω	COM, 4 Ω
Output(V):	70V, 100V	70V, 100V
Power supply/Consumption:	AC 115V/230V,50/60Hz	AC 115V/230V,50/60Hz
Dimensions	480x470x133mm	480x470x133mm
(WxDxH):	(18.9"x18.5"x5.2")	(18.9"x18.5"x5.2")
Weight:	17.6kg (38.80 lb)	17.6kg (38.80 lb)