

Driver Units

TU SERIES

TU-35 / 60 / 100 / MT-35 / 60 / 100



TU-35



TU-60



TU-100



MT-35



MT-60



MT-100

Driver units

The driver unit in die-cast aluminium.

Pantone No.: Cool gray 6C

Models are equally suited for application with SHOW projector horns or as replacement drivers for using with standard 1 3/8"-18 male thread horns. High power and high effect. It provides highly articulated sound in any harsh environment.

MODEL	TU-35	TU-60	TU-100	TU-150
Input Power (RMS)	35W	60W	100W	150W
Impedance	16 Ω	16 Ω	16 Ω	16 Ω
Frequency Response	150Hz~6KHz	150Hz-6KHz	100Hz-10KHz	100Hz-10KHz
S.P.L	110dB (1W/M) with TH-16	112dB (1W/M) with TH-16	112dB (1W/M) with TH-16	114dB (1W/M) with TH-16
Dimension	ϕ 106 \times 110mm (ϕ 4.2" \times 4.3")	ϕ 114 \times 112mm (ϕ 4.5" \times 4.4")	ϕ 120 \times 123mm (ϕ 4.7" \times 4.8")	ϕ 116 \times 100mm (ϕ 4.6" \times 3.9")
Weight (Approx.)	1.4kg (3.09 lb)	1.65kg (3.64 lb)	2.1kg (4.63 lb)	4.02kg (8.86 lb)

MODEL	MT-35	MT-60	MT-100
Input Power (RMS)	35W (with transformer)	60W (with transformer)	100W (with transformer)
Input Voltage	100V	100V	100V
Impedance: (\pm 20%)	290 Ω (35W)/ 500 Ω (20W)/ 1K Ω (10W)	170 Ω (60W)/ 250 Ω (40W)/ 500 Ω (20W)	100 Ω (100W)/ 200 Ω (50W)/ 286 Ω (35W)
Frequency Response	150Hz~6KHz (-20dB)	150Hz~6KHz (-20dB)	100Hz~6KHz (-20dB)
S.P.L: (\pm 3dB)	114dB (1W/M)	114dB (1W/M)	114dB (1W/M)
Material	Aluminum cover / Plastics base	Aluminum cover / Plastics base	Aluminum cover / Plastics base
Dimension	ϕ 130 \times 137.5mm	ϕ 130 \times 137.5mm	ϕ 160 \times 147.5mm
Weight (Approx.)	1.9kg (4.19 lb)	2.50kg (6 lb)	3.16kg(6.97 lb)